

Amendments to the Specification:

Please replace paragraph [0060] with the following rewritten paragraph:

[0060] Fig. 1 is a schematic of a liquid crystal display device according to this exemplary embodiment. In a liquid crystal cell 4, a semi-transparent reflective layer is provided on a lower substrate, and the thickness of a liquid crystal layer is made different between a transmissive display region and a reflective display region by a layer-thickness adjusting layer. Regarding cell parameters, the retardation $\Delta n \cdot d$ is 0.32 micrometer in the transmissive display region and the retardation $\Delta n \cdot d$ is 0.14 micrometer in the reflective display region, the alignment of the liquid crystal is homogeneous, and the twist angle is set at zero degrees. A polarizing plate 1 is disposed over the upper side of the liquid crystal cell 4, a uniaxially stretched phase difference film 2 is interposed between the polarizing plate 1 and the liquid crystal cell 4, and a liquid crystal film 3 fixed in nematic hybrid alignment is interposed between the phase difference film 2 and the liquid crystal cell 4. In this case, the angles θ_1 , θ_2 , and θ_3 are formed respectively with reference to a rubbing axis 41 for the upper substrate of the liquid crystal cell 4, ~~the rubbing axis 41 being equal to the distinct viewing direction in this embodiment:~~ cell 4: the angle θ_1 is formed between the rubbing axis 41 and a transmission axis 11 of the polarization plate 1; the angle θ_2 is formed between the rubbing axis 41 and a phase-retarding axis 21 of the phase difference film 2; the angle θ_3 is formed between the rubbing axis 41 and a phase-retarding axis 31 of the liquid crystal film 3. θ_1 is 4 degrees, θ_2 is 115 degrees, and θ_3 is zero degrees. Furthermore, the retardation $\Delta n \cdot d$ of the phase difference film 2 is approximately 0.25 micrometer, and the retardation $\Delta n \cdot d$ of the liquid crystal film 3 is approximately 0.09 micrometer.

Please replace paragraph [0063] with the following rewritten paragraph:

[0063] Also, a polarizing plate 7 is disposed under the lower side of the liquid crystal cell 4, a phase difference film 6 is interposed between the polarizing plate 7 and the liquid crystal cell 4, and a liquid crystal film 5 fixed in nematic hybrid alignment is interposed between the phase difference film 6 and the liquid crystal cell 4. In this case, the angles θ_5 , θ_6 , and θ_7 are formed respectively with reference to a rubbing-axis 41- axis 42 for the ~~upper~~ lower substrate of the liquid crystal cell 4: the angle θ_5 is formed between the rubbing-axis 41- axis 42 and a phase-retarding axis 51 of the liquid crystal film 5; the angle θ_6 is formed between the rubbing-axis 41- axis 42 and a phase-retarding axis 61 of the phase difference film 6; the angle θ_7 is formed between the rubbing -axis 41-axis 42 and a transmission axis 71 of the polarizing plate 7. θ_5 is zero degrees, θ_6 is 66 degrees, and θ_7 is 88 degrees. Furthermore, the retardation $\Delta n \cdot d$ of the phase difference film 6 is approximately 0.26 micrometer, and the retardation $\Delta n \cdot d$ of the liquid crystal film 5 is approximately 0.09 micrometer.